

Rifle Reloading data

Cartridge

Cartridge .30-06 Springfield
Test barrel 620 mm (24½"), 1 in 10" twist
Primers Large Rifle
Cases Lapua, trim-to length 63,10 mm (2.484")



VIHTAVUORI

Bullet specifications

Your search returned **323** different loads:

Bullet				Powder	Load			
g			mm		g			
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
3,7	Lapua	ALS	79,0	N110	2,02	2,49	1075	1217
6,5	Lapua	HP / OTCE	79,8	N130	2,58	3,15	869	998
6,5	Lapua	HP / OTCE	79,8	N133	3,07	3,49	911	1016
6,5	Lapua	HP / OTCE	79,8	N135	3,25	3,66	927	1033
6,5	Lapua	HP / OTCE	79,8	N140	3,50	3,96	926	1044
6,5	Lapua	HP / OTCE	79,8	N540	3,59	4,08	939	1058
7,1	Hornady	RN	74,0	N133	3,15	3,48	873	983
7,1	Hornady	RN	74,0	N135	3,14	3,47	864	964
7,1	Hornady	RN	74,0	N140	3,38	3,74	881	977
7,1	Hornady	RN	74,0	N150	3,57	3,94	905	1002
8,0	Lapua	FMJ	79,8	N130	2,61	3,01	838	934
8,0	Lapua	FMJ	79,8	N133	2,95	3,31	825	922
8,0	Lapua	FMJ	79,8	N135	3,19	3,48	852	937
8,0	Lapua	FMJ	79,8	N140	3,35	3,73	853	952
8,0	Lapua	FMJ	79,8	N540	3,49	3,83	863	958
8,0	Lapua	FMJ	79,8	N150	3,59	3,91	880	976
8,1	Hornady	ECX	81,1	N135	2,70	2,92	807	883
8,1	Hornady	ECX	81,1	N140	3,20	3,43	870	937
8,1	Hornady	ECX	81,1	N540	3,30	3,60	880	965
8,1	Hornady	ECX	81,1	N150	3,15	3,47	856	936
8,1	Hornady	ECX	81,1	N550	3,45	3,80	890	970
8,1	Hornady	ECX	81,1	N555	3,80	3,90	891	915
8,1	Hornady	ECX	81,1	N160	3,85	4,10	886	942
8,1	Nosler	Ballistic Tip	84,0	N135	3,10	3,40	865	935
8,1	Nosler	Ballistic Tip	84,0	N140	3,31	3,64	878	958
8,1	Nosler	Ballistic Tip	84,0	N540	3,49	3,91	880	994

Bullet				Powder	Load			
g			mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
8,1	Nosler	Ballistic Tip	84,0	N150	3,34	3,81	882	966
8,1	Nosler	Ballistic Tip	84,0	N550	3,70	3,91	895	950
8,5	Barnes	TSX BT	83,3	N530	3,03	3,34	860	935
8,5	Barnes	TSX BT	83,3	N140	3,20	3,47	864	936
8,5	Barnes	TSX BT	83,3	N540	3,33	3,62	883	960
8,5	Barnes	TSX BT	83,3	N150	3,25	3,55	868	938
8,5	Barnes	TSX BT	83,3	N550	3,54	3,89	882	967
9,5	Brenneke	TUG	80,8	N140	2,94	3,22	773	850
9,5	Brenneke	TUG	80,8	N540	3,09	3,40	804	888
9,5	Brenneke	TUG	80,8	N150	3,07	3,37	790	867
9,5	Brenneke	TUG	80,8	N550	3,25	3,60	806	893
9,5	Brenneke	TUG	80,8	N555	3,72	3,90	845	882
9,5	Brenneke	TUG	80,8	N160	3,80	4,13	824	910
9,7	Barnes	TTSX BT	84,8	N150	2,94	3,21	780	851
9,7	Barnes	TTSX BT	84,8	N550	3,20	3,52	799	880
9,7	Barnes	TTSX BT	84,8	N555	3,60	3,96	836	909
9,7	Barnes	TTSX BT	84,8	N160	3,68	4,00	819	892
9,7	Hornady	SST	82,6	N530	2,82	3,10	808	874
9,7	Hornady	SST	82,6	N140	3,05	3,27	824	882
9,7	Hornady	SST	82,6	N540	3,15	3,39	839	906
9,7	Hornady	SST	82,6	N150	3,08	3,33	828	891
9,7	Hornady	SST	82,6	N550	3,36	3,58	838	903
9,7	Hornady	SST	82,6	N555	3,70	4,00	846	903
9,7	Hornady	SST	82,6	N160	3,66	3,92	854	918
9,7	Lapua	LockBase	84,0	N135	2,93	3,23	789	851
9,7	Lapua	LockBase	84,0	N140	3,13	3,45	802	872
9,7	Lapua	LockBase	84,0	N540	3,16	3,54	792	882
9,7	Lapua	LockBase	84,0	N150	3,25	3,58	803	877
9,7	Lapua	LockBase	84,0	N550	3,51	3,87	819	917
9,7	Lapua	Mega E469	76,9	N135	2,60	3,09	711	835
9,7	Lapua	Mega E469	76,9	N140	2,83	3,32	732	857
9,7	Lapua	Mega E469	76,9	N540	2,94	3,47	742	893
9,7	Lapua	Mega E469	76,9	N150	2,86	3,22	777	858
9,7	Lapua	Mega E469	76,9	N550	3,12	3,48	801	886
9,7	LOS	HT	83,0	N540	3,21	3,50	864	940
9,7	LOS	HT	83,0	N150	3,21	3,49	853	922
9,7	LOS	HT	83,0	N550	3,40	3,80	866	952
9,7	Norma	FMJ	82,0	N540	3,10	3,42	826	904

Bullet				Powder	Load			
g			mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
9,7	Norma	FMJ	82,0	N150	3,10	3,36	822	884
9,7	Norma	FMJ	82,0	N550	3,35	3,59	834	904
9,7	Norma	FMJ	82,0	N555	3,70	3,95	863	918
9,7	Norma	FMJ	82,0	N160	3,65	3,90	810	870
9,7	Red Moose	TARVAS	82,9	N140	3,27	3,48	838	897
9,7	Red Moose	TARVAS	82,9	N540	3,40	3,62	855	925
9,7	Red Moose	TARVAS	82,9	N150	3,30	3,54	832	896
9,7	Red Moose	TARVAS	82,9	N550	3,60	3,83	867	930
9,7	Sierra	HPBT	84,0	N140	3,08	3,42	798	871
9,7	Sierra	HPBT	84,0	N540	3,27	3,64	809	906
9,7	Sierra	HPBT	84,0	N150	3,29	3,65	807	895
9,7	Sierra	HPBT	84,0	N550	3,54	3,87	833	916
10,0	Brenneke	TAG	81,8	N150	2,89	3,25	760	842
10,0	Brenneke	TAG	81,8	N550	3,28	3,52	796	868
10,0	Brenneke	TAG	81,8	N160	3,43	3,75	784	844
10,0	Lapua	Scenar / OTM Scenar-L	84,0	N140	2,78	3,23	755	850
10,0	Lapua	Scenar / OTM Scenar-L	84,0	N540	3,05	3,45	774	886
10,0	Lapua	Scenar / OTM Scenar-L	84,0	N150	2,79	3,30	767	863
10,0	Lapua	Scenar / OTM Scenar-L	84,0	N550	3,19	3,48	811	899
10,0	Lapua	Scenar / OTM Scenar-L	84,0	N160	3,45	3,77	817	902
10,0	Nosler	Custom Competition	84,8	N140	2,88	3,18	791	856
10,0	Nosler	Custom Competition	84,8	N540	3,08	3,39	822	893
10,0	Nosler	Custom Competition	84,8	N150	2,92	3,22	803	867
10,0	Nosler	Custom Competition	84,8	N550	3,28	3,57	831	900
10,0	Nosler	Custom Competition	84,8	N555	3,60	3,90	848	912
10,0	Nosler	Custom Competition	84,8	N160	3,65	3,93	836	899
10,0	Sierra	HPBT Palma	84,8	N140	3,10	3,34	821	876
10,0	Sierra	HPBT Palma	84,8	N540	3,16	3,41	829	898
10,0	Sierra	HPBT Palma	84,8	N150	3,12	3,33	821	879
10,0	Sierra	HPBT Palma	84,8	N550	3,45	3,64	843	902
10,0	Sierra	HPBT Palma	84,8	N160	3,67	3,90	845	896
10,1	Berger	Fullbore	83,5	N140	3,07	3,31	808	870
10,1	Berger	Fullbore	83,5	N540	3,19	3,42	834	903
10,1	Berger	Fullbore	83,5	N150	3,10	3,34	823	880
10,1	Berger	Fullbore	83,5	N550	3,35	3,57	842	903
10,1	Berger	Fullbore	83,5	N555	3,65	3,95	851	906
10,1	Berger	Fullbore	83,5	N160	3,75	3,98	846	908
10,7	Brenneke	TOG	81,0	N150	2,50	2,90	682	764

Bullet				Powder	Load			
g			mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
10,7	Brenneke	TOG	81,0	N550	2,96	3,33	738	816
10,7	Brenneke	TOG	81,0	N555	3,40	3,85	767	860
10,7	Brenneke	TOG	81,0	N160	2,90	3,53	708	810
10,7	Hornady	ECX	81,1	N140	2,75	3,05	711	786
10,7	Hornady	ECX	81,1	N540	2,90	3,18	738	820
10,7	Hornady	ECX	81,1	N150	2,70	3,11	706	792
10,7	Hornady	ECX	81,1	N550	3,05	3,31	758	826
10,7	Hornady	ECX	81,1	N555	3,28	3,71	770	845
10,7	Hornady	ECX	81,1	N160	3,30	3,75	747	834
10,7	Hornady	ECX	81,1	N560	3,65	4,10	767	857
10,7	Hornady	GMX	83,5	N550	2,93	3,13	747	812
10,7	Hornady	GMX	83,5	N555	3,19	3,49	769	831
10,7	Hornady	GMX	83,5	N160	3,04	3,46	740	824
10,7	Hornady	GMX	83,5	N560	3,36	3,61	742	816
10,7	Red Moose	TARVAS	82,8	N540	3,27	3,48	811	877
10,7	Red Moose	TARVAS	82,8	N150	3,13	3,36	782	841
10,7	Red Moose	TARVAS	82,8	N550	3,42	3,65	814	876
10,7	Red Moose	TARVAS	82,8	N555	3,77	4,05	837	883
10,7	Red Moose	TARVAS	82,8	N160	3,81	4,10	819	882
10,7	Sierra	SBT	84,3	N540	3,12	3,39	804	868
10,7	Sierra	SBT	84,3	N150	2,96	3,26	770	833
10,7	Sierra	SBT	84,3	N550	3,27	3,54	808	873
10,7	Sierra	SBT	84,3	N555	3,67	3,90	831	879
10,7	Sierra	SBT	84,3	N160	3,60	3,95	808	874
10,7	Swift	Scirocco II	84,0	N540	2,98	3,23	768	835
10,7	Swift	Scirocco II	84,0	N150	2,80	3,12	751	813
10,7	Swift	Scirocco II	84,0	N550	3,21	3,46	782	848
10,7	Swift	Scirocco II	84,0	N555	3,34	3,73	788	862
10,7	Swift	Scirocco II	84,0	N160	3,41	3,67	788	849
10,7	Swift	Scirocco II	84,0	N560	3,62	3,95	778	852
10,85	Lapua	Scenar	84,0	N135	2,75	3,02	746	808
10,85	Lapua	Scenar	84,0	N140	2,95	3,25	737	812
10,85	Lapua	Scenar	84,0	N540	2,94	3,37	737	836
10,85	Lapua	Scenar	84,0	N150	3,06	3,38	748	821
10,85	Lapua	Scenar	84,0	N550	3,22	3,57	779	855
10,85	Lapua	Scenar	84,0	N160	3,60	4,00	749	842
10,9	Barnes	TSX	81,7	N540	2,73	3,09	735	824
10,9	Barnes	TSX	81,7	N550	2,96	3,26	735	825

Bullet				Powder	Load			
g			mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
10,9	Barnes	TSX	81,7	N160	3,25	3,65	745	833
10,9	Berger	Classic Hunter	82,8	N140	2,82	3,08	761	826
10,9	Berger	Classic Hunter	82,8	N540	3,00	3,25	789	854
10,9	Berger	Classic Hunter	82,8	N150	2,87	3,14	774	837
10,9	Berger	Classic Hunter	82,8	N550	3,12	3,37	792	855
10,9	Berger	Classic Hunter	82,8	N555	3,45	3,79	808	878
10,9	Berger	Classic Hunter	82,8	N160	3,53	3,80	805	870
10,9	Hornady	A-Max	81,8	N540	3,02	3,23	778	842
10,9	Hornady	A-Max	81,8	N150	2,95	3,19	762	823
10,9	Hornady	A-Max	81,8	N550	3,27	3,46	794	855
10,9	Hornady	A-Max	81,8	N555	3,50	3,80	802	866
10,9	Hornady	A-Max	81,8	N160	3,65	3,94	801	858
10,9	Nosler	RDF	84,8	N140	2,85	3,12	760	822
10,9	Nosler	RDF	84,8	N540	3,02	3,20	792	846
10,9	Nosler	RDF	84,8	N150	2,90	3,14	775	830
10,9	Nosler	RDF	84,8	N550	3,10	3,35	791	857
10,9	Nosler	RDF	84,8	N555	3,50	3,78	815	877
10,9	Nosler	RDF	84,8	N160	3,55	3,81	808	868
10,9	Sierra	TMK	84,0	N140	2,89	3,16	762	832
10,9	Sierra	TMK	84,0	N540	2,98	3,24	790	864
10,9	Sierra	TMK	84,0	N150	2,95	3,22	774	845
10,9	Sierra	TMK	84,0	N550	3,17	3,46	800	876
11,0	Lapua	LockBase B476	84,0	N140	2,91	3,24	717	799
11,0	Lapua	LockBase B476	84,0	N540	2,96	3,34	729	821
11,0	Lapua	LockBase B476	84,0	N150	3,06	3,41	735	815
11,0	Lapua	LockBase B476	84,0	N550	3,17	3,61	746	842
11,0	Lapua	LockBase B476	84,0	N160	3,65	4,05	765	853
11,0	Lapua	Naturalis LR	82,0	N150	2,54	3,12	753	822
11,0	Lapua	Naturalis LR	82,0	N550	3,16	3,42	761	845
11,0	Lapua	Naturalis LR	82,0	N160	3,39	3,74	756	846
11,0	Lapua	Naturalis N558	82,0	N540	2,85	3,15	739	821
11,0	Lapua	Naturalis N558	82,0	N150	2,62	2,99	694	771
11,0	Lapua	Naturalis N558	82,0	N550	3,01	3,33	759	843
11,0	Lapua	Naturalis N558	82,0	N555	3,43	3,68	786	846
11,0	Lapua	Naturalis N558	82,0	N160	3,38	3,73	777	857
11,0	Lapua	Naturalis N558	82,0	N560	3,47	3,91	756	846
11,0	Sako	Blade 657A	84,8	N140	2,67	3,03	667	758
11,0	Sako	Blade 657A	84,8	N540	2,90	3,24	736	820

Bullet				Powder	Load			
g				mm		g		m/s
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
11,0	Sako	Blade 657A	84,8	N150	2,70	3,09	676	764
11,0	Sako	Blade 657A	84,8	N550	3,08	3,40	742	825
11,0	Sako	Blade 657A	84,8	N555	3,38	3,82	766	848
11,0	Sako	Blade 657A	84,8	N160	3,25	3,74	721	817
11,3	Lapua	OTM Scenar-L GB550	84,6	N540	3,03	3,26	760	829
11,3	Lapua	OTM Scenar-L GB550	84,6	N150	3,00	3,21	751	807
11,3	Lapua	OTM Scenar-L GB550	84,6	N550	3,30	3,45	777	833
11,3	Lapua	OTM Scenar-L GB550	84,6	N555	3,45	3,71	787	843
11,3	Lapua	OTM Scenar-L GB550	84,6	N160	3,60	3,82	777	835
11,3	Lapua	OTM Scenar-L GB550	84,6	N560	3,67	3,95	767	836
11,6	Hornady	ELD-X	84,8	N540	3,01	3,28	764	837
11,6	Hornady	ELD-X	84,8	N150	3,02	3,26	744	814
11,6	Hornady	ELD-X	84,8	N550	3,19	3,44	766	839
11,6	Hornady	ELD-X	84,8	N555	3,41	3,69	774	833
11,6	Hornady	ELD-X	84,8	N160	3,51	3,88	765	843
11,7	Barnes	TSX	81,7	N540	2,72	2,99	713	783
11,7	Barnes	TSX	81,7	N550	2,89	3,20	710	788
11,7	Barnes	TSX	81,7	N160	3,14	3,54	712	792
11,7	Berger	Elite Hunter	84,8	N540	3,05	3,31	783	850
11,7	Berger	Elite Hunter	84,8	N150	2,99	3,26	761	825
11,7	Berger	Elite Hunter	84,8	N550	3,28	3,52	785	859
11,7	Berger	Elite Hunter	84,8	N555	3,48	3,75	783	845
11,7	Berger	Elite Hunter	84,8	N160	3,54	3,91	788	862
11,7	Berger	Elite Hunter	84,8	N560	3,71	4,08	785	866
11,7	Fox Bullets	Classic Hunter	80,0	N140	2,60	2,84	701	751
11,7	Fox Bullets	Classic Hunter	80,0	N540	2,73	3,06	722	794
11,7	Fox Bullets	Classic Hunter	80,0	N150	2,55	2,85	688	756
11,7	Fox Bullets	Classic Hunter	80,0	N160	3,31	3,68	739	816
11,7	Hornady	CX	81,7	N540	2,70	3,01	697	772
11,7	Hornady	CX	81,7	N150	2,60	2,93	666	739
11,7	Hornady	CX	81,7	N550	2,75	3,11	691	771
11,7	Hornady	CX	81,7	N555	3,20	3,68	728	810
11,7	Hornady	CX	81,7	N160	3,00	3,53	692	782
11,7	Hornady	CX	81,7	N560	3,60	3,93	745	815
11,7	Hornady	GMX	82,9	N140	2,68	2,88	687	737
11,7	Hornady	GMX	82,9	N540	2,71	2,94	697	751
11,7	Hornady	GMX	82,9	N150	2,58	2,91	666	742
11,7	Hornady	GMX	82,9	N550	2,83	3,13	695	773

Bullet				Powder	Load			
g			mm		g		m/s	
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
11,7	Hornady	GMX	82,9	N555	3,15	3,56	728	800
11,7	Hornady	GMX	82,9	N160	2,97	3,41	695	779
11,7	Hornady	GMX	82,9	N560	3,47	3,96	716	807
11,7	Norma	Oryx	82,0	N150	2,66	2,98	719	779
11,7	Norma	Oryx	82,0	N550	2,86	3,14	732	796
11,7	Norma	Oryx	82,0	N160	3,21	3,61	748	819
11,7	Norma	Oryx	82,0	N560	3,44	3,74	748	816
11,7	Sierra	SBT	84,6	N540	2,94	3,19	747	813
11,7	Sierra	SBT	84,6	N150	2,86	3,19	733	796
11,7	Sierra	SBT	84,6	N550	3,12	3,38	763	826
11,7	Sierra	SBT	84,6	N555	3,50	3,85	788	856
11,7	Sierra	SBT	84,6	N160	3,54	3,82	769	832
12,0	Berger	Classic Hunter	84,6	N540	3,10	3,36	776	842
12,0	Berger	Classic Hunter	84,6	N150	3,01	3,31	750	820
12,0	Berger	Classic Hunter	84,6	N550	3,30	3,53	775	846
12,0	Berger	Classic Hunter	84,6	N555	3,49	3,72	774	828
12,0	Berger	Classic Hunter	84,6	N160	3,57	3,89	772	848
12,0	Berger	Classic Hunter	84,6	N560	3,77	4,11	778	860
12,0	Berger	Hybrid Target	84,0	N150	2,96	3,21	746	813
12,0	Berger	Hybrid Target	84,0	N550	3,19	3,41	773	840
12,0	Berger	Hybrid Target	84,0	N160	3,49	3,85	767	842
12,0	Berger	Hybrid Target	84,0	N560	3,64	3,98	765	850
12,0	Berger	Juggernaut Target	84,8	N540	2,95	3,15	752	809
12,0	Berger	Juggernaut Target	84,8	N150	2,70	3,04	719	783
12,0	Berger	Juggernaut Target	84,8	N550	3,00	3,29	748	815
12,0	Berger	Juggernaut Target	84,8	N555	3,45	3,73	780	836
12,0	Berger	Juggernaut Target	84,8	N160	3,35	3,73	757	825
12,0	Berger	Juggernaut Target	84,8	N560	3,60	3,95	765	841
12,0	Brenneke	Basic	81,0	N540	2,88	3,21	734	806
12,0	Brenneke	Basic	81,0	N550	3,08	3,30	746	804
12,0	Brenneke	Basic	81,0	N555	3,47	3,78	767	829
12,0	Brenneke	Basic	81,0	N160	3,42	3,69	750	812
12,0	Lapua	Mega E415	79,5	N540	2,82	3,17	728	811
12,0	Lapua	Mega E415	79,5	N150	2,75	3,28	692	791
12,0	Lapua	Mega E415	79,5	N550	3,12	3,46	728	812
12,0	Lapua	Mega E415	79,5	N160	3,38	3,71	739	815
12,0	Lapua	Mega E415	79,5	N560	3,50	3,89	737	826
12,0	Lapua	Scenar	84,0	N540	2,86	3,16	688	771

Bullet				Powder	Load			
g				mm		g		m/s
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
12,0	Lapua	Scenar	84,0	N150	2,88	3,26	696	778
12,0	Lapua	Scenar	84,0	N550	3,02	3,36	701	792
12,0	Lapua	Scenar	84,0	N160	3,48	3,85	724	809
12,0	Lapua	Scenar	84,0	N560	3,52	4,01	724	816
12,3	Sierra	HPBT	84,0	N150	2,90	3,20	695	767
12,3	Sierra	HPBT	84,0	N550	3,07	3,49	708	812
12,3	Sierra	HPBT	84,0	N555	3,40	3,75	757	824
12,3	Sierra	HPBT	84,0	N160	3,42	3,81	724	795
12,3	Sierra	HPBT	84,0	N560	3,57	4,04	721	825
13,0	Lapua	Mega E401	79,5	N150	2,75	3,10	692	747
13,0	Lapua	Mega E401	79,5	N550	3,12	3,28	730	767
13,0	Lapua	Mega E401	79,5	N555	3,37	3,67	730	794
13,0	Lapua	Mega E401	79,5	N160	3,38	3,48	739	763
13,0	Nosler	Partition	84,0	N150	2,79	3,08	669	724
13,0	Nosler	Partition	84,0	N160	3,38	3,73	704	765
13,0	Rhino	Solid Shank Scandinavia	78,0	N540	2,70	3,05	670	748
13,0	Rhino	Solid Shank Scandinavia	78,0	N150	2,59	3,03	650	731
13,0	Rhino	Solid Shank Scandinavia	78,0	N550	3,00	3,35	703	774
13,0	Rhino	Solid Shank Scandinavia	78,0	N555	3,45	3,77	736	797
13,0	Rhino	Solid Shank Scandinavia	78,0	N160	3,45	3,67	717	774
13,0	Swift	A-Frame	84,0	N550	3,19	3,42	720	784
13,0	Swift	A-Frame	84,0	N160	3,40	3,68	708	778
13,0	Swift	A-Frame	84,0	N165	3,85	4,14	740	804
13,3	Berger	Elite Hunter	84,5	N140	2,73	2,96	684	741
13,3	Berger	Elite Hunter	84,5	N540	2,87	3,11	708	766
13,3	Berger	Elite Hunter	84,5	N150	2,80	3,04	687	742
13,3	Berger	Elite Hunter	84,5	N550	3,00	3,23	714	772
13,3	Berger	Elite Hunter	84,5	N555	3,33	3,63	733	794
13,3	Berger	Elite Hunter	84,5	N160	3,39	3,65	722	780
13,5	Berger	Long Range Hybrid Target	84,8	N140	2,72	2,90	678	726
13,5	Berger	Long Range Hybrid Target	84,8	N540	2,82	3,02	698	756
13,5	Berger	Long Range Hybrid Target	84,8	N150	2,75	2,98	677	733
13,5	Berger	Long Range Hybrid Target	84,8	N550	2,95	3,19	705	765
13,5	Berger	Long Range Hybrid Target	84,8	N555	3,38	3,63	734	788
13,5	Berger	Long Range Hybrid Target	84,8	N160	3,40	3,65	718	779
13,5	Hornady	A-MAX	84,2	N550	3,03	3,28	711	769
13,5	Hornady	A-MAX	84,2	N160	3,27	3,56	711	774
13,5	Hornady	A-MAX	84,2	N560	3,56	3,83	732	798

Bullet				Powder	Load			
g				mm		g		m/s
Weight	Mfg	Type	C.O.L	Type	Weight		Velocity	
					start	max	start	max
13,5	Hornady	A-MAX	84,2	N565	3,57	3,89	729	782
13,6	Nosler	RDF	84,8	N140	2,70	2,85	685	721
13,6	Nosler	RDF	84,8	N150	2,60	2,88	670	727
13,6	Nosler	RDF	84,8	N550	2,85	3,08	692	752
13,6	Nosler	RDF	84,8	N555	3,15	3,44	713	774
13,6	Nosler	RDF	84,8	N160	3,20	3,47	708	766
13,6	Nosler	RDF	84,8	N560	3,35	3,61	712	774
14,0	Berger	Hybrid Target	84,8	N550	3,04	3,28	704	768
14,0	Berger	Hybrid Target	84,8	N555	3,25	3,53	705	761
14,0	Berger	Hybrid Target	84,8	N165	3,76	3,95	727	774
14,0	Berger	Hybrid Target	84,8	N560	3,55	3,94	719	800
14,3	Berger	Long Range Hybrid Target	84,8	N150	2,68	2,89	652	702
14,3	Berger	Long Range Hybrid Target	84,8	N550	2,87	3,13	679	740
14,3	Berger	Long Range Hybrid Target	84,8	N555	3,32	3,58	711	767
14,3	Berger	Long Range Hybrid Target	84,8	N160	3,30	3,53	693	750
14,3	Hornady	RN	84,0	N160	3,29	3,63	654	722
14,3	Hornady	RN	84,0	N560	3,47	3,97	672	767
14,3	Lapua	Scenar-L	84,8	N150	2,71	2,96	645	701
14,3	Lapua	Scenar-L	84,8	N550	3,00	3,18	679	735
14,3	Lapua	Scenar-L	84,8	N555	3,15	3,42	686	741
14,3	Lapua	Scenar-L	84,8	N160	3,20	3,54	674	734
14,3	Lapua	Scenar-L	84,8	N165	3,60	3,89	700	760
14,3	Lapua	Scenar-L	84,8	N560	3,42	3,71	684	751
14,3	Rhino	Solid Shank	81,6	N150	2,66	2,93	632	686
14,3	Rhino	Solid Shank	81,6	N550	2,98	3,15	665	713
14,3	Rhino	Solid Shank	81,6	N160	3,20	3,45	672	725
14,3	Rhino	Solid Shank	81,6	N560	3,48	3,88	680	752
14,3	Rhino	Solid Shank	81,6	N565	3,75	3,99	697	750
15,6	Woodleigh	Weldcore	84,0	N165	3,45	3,90	658	729
15,6	Woodleigh	Weldcore	84,0	N560	3,31	3,67	647	726
15,6	Woodleigh	Weldcore	84,0	N565	3,48	3,87	667	732